


Flanged Eyelet List in Ascending Hub Diameter "D"

Represented by Sigma Cable and Wire solutions

sigmacws@mweb.co.za



Material Legend

% The percentage of Alumina Content

Ti Titania (TiO₂)
WC Tungsten Carbide

	D	A	B	C	E	R	Wt. g	Material
E013	1.5	2	0.3	2	1.5	0.06	1.00	WC
E136	1.8	2.6	0.8	11.5	10.5	0.25	0.09	95%
E305	1.8	2.3	1	6.5	5.2 V		0.05	95%
E142	2	3.1	0.8	6.6	5.5	1	0.07	95%
E069	2	3.1	0.9	3	2	0.8	0.04	90%
E137	2	2.5	1.1	16	14.8	0.5	0.12	95%
E181	2.1	3.1	1	2	1.2	0.5	0.03	95%
E225	2.5	3.8	1.4	7	6	1	0.12	95%
E289	2.5	3.8	1.5	8.3	6.9 V		0.10	95%
E358	2.6	4.4	1	3	2	1.5	0.50	99%
E183	2.6	3.8	1.2	6.1	5	1	0.11	95%
E017	2.6	3.8	1.5	4	3	1.25	0.05	90%
E177	2.7	4.5	0.65	3	2	2	0.09	99%
E025	2.7	4.4	0.9	3	2	1.5	0.05	99%
E182	2.8	3.9	0.9	4.2	3	0.25	0.11	95%
E070	2.8	3.9	1	4.2	3	0.25	0.12	95%
E073	2.8	4.7	1.2	4.2	3	1	0.12	99%
E184	2.9	4.8	1.2	2.2	1	1.25	0.09	95%
E072	2.9	4.8	1.2	3.3	2.1	1	0.12	95%
E322	3	4.3	1.9	10	8.8 V		0.20	99%
E212	3	4.2	2	3.9	3	0.5	0.07	95%
E324	3	4.3	2	4.8	4	1	0.06	95%
E323	3	4.3	2	8.2	5.2	0.5	0.18	99%
E075	3.1	4.2	1.6	3	2	1	0.08	95%
E074	3.3	5.7	1.6	4.8	3.6	1	0.18	95%
E141	3.7	6	1.8	3.7	2.6	1.5	0.17	95%
E390	3.7	4.7	1.8	4.8	3.6	0.5	0.15	92%
E026	3.7	5.9	1.9	3.5	2.5	1.5	0.15	99%
E076	3.7	5.5	1.9	5.2	4	1	0.19	95%
E004	3.7	6.9	2	4	2.5	1.5	0.25	99%

Part No. D A B C E R Wt. g Material

TE026	3.8	6	1.8	3.5	2.5	0.5	1.00	WC	
E349	3.8	5.5	2	5.4	4.3	1	0.20	Ti	
E236	3.9	7	1.6	4.1	2.6	1.5	0.22		95%
E140	3.9	6	1.9	3.5	2.5	1.25	0.15		99%
E077	3.9	5.5	2	4.3	3	1	0.18		95%
E286	3.9	5.8	2	4.4	2.4	1.25	0.20		99%
E109	3.9	5.9	2	4.5	2.6	1.5	0.22		95%
E187	4	6	2.4	6	5	1.25	0.23		95%
E015	4.1	5	2.6	4	3.1	1	0.15		95%
E134	4.1	5	2.6	5	4	1	0.15		95%
E188	4.2	6	2.5	3.5	2.5	1.25	0.20		99%
E081	4.2	5.7	2.5	5.7	4.6	1.25	0.23	Ti	
E016	4.3	5.9	2	5	3.5	1	0.25		95%
E018	4.3	5.9	2	7.1	5.9	1.25	0.35		95%
E078	4.3	5.9	2	9.1	7.8	1	0.21		95%
E039	4.7	6.6	2.9	4.2	3	1.25	0.25		95%
E085	4.7	6.4	3.2	8	6.5	1	0.32		95%
E272	4.8	6.7	3	4.2	3.1	1.25	0.20		95%
E087	4.8	6.4	3.3	6.7	5.4	1	0.30		95%
E189	4.9	7	3	6	4.6	1.25	0.36		99%
E139	4.9	6.4	3.2	4	3	1.25	0.20		99%
E360	5	6.5	2	4	2.9	1	0.27		95%
E027	5	6.7	3	3.9	3	1.5	0.20		99%
TE003	5	8	3.2	5	3.5	2	1.00	WC	
E079	5.1	6.6	2	8	6.5	1.25	0.56		95%
E273	5.1	6.5	2	12.8	11.3	1.5	0.85		95%
E082	5.1	7	2.3	4.7	3.1	1	0.40	Ti	
E086	5.1	6.8	3.2	5.5	4	1.25	0.34	Ti	

Part No.	D	A	B	C	E	R	Wt. g	Material	
E089	5.2	6.8	3.3	5.4	4	1	0.30		95%
E019	5.7	8	2.7	5.4	3.8	2.25	0.45		99%
E014	5.7	7.7	2.9	7.5	5.5	1.5	0.70		99%
E012	5.8	7.8	3.5	6	4.2	1	0.50		99%
E090	5.9	7.8	3.4	4.9	2.9	1	0.48	Ti	
E005	5.9	7.8	3.4	6	4.1	1	0.55		95%
E293	5.9	7.9	3.4	6.5	5	1.5	0.50		95%
E269	5.9	7.9	3.4	9.4	7.4	1.5	0.74		95%
E192	6	8	3.4	4.5	3.5	2	0.35		99%
E056	6.1	8.8	3.5	7.9	6.4	1.25	0.66		90%
E021	6.1	8.4	4	8.1	6.6	1.25	0.60		95%
E239	6.2	7.9	3.6	11.8	9.8	0.25	0.93		95%
E093	6.2	8.4	3.9	8.2	6.7	1	0.65		95%
E193	6.2	7.8	4	4.5	3.5	1.25	0.33		99%
E044	6.3	10.7	2.9	15	12	2	1.90		90%
E122	6.3	8.3	3.3	8	5.4	1	0.77		95%
E094	6.4	8.6	3.9	4.6	3.2	1.25	0.42		95%
E321	6.4	8.8	4.1	9	6	1.5	0.90		95%
E092	6.7	8.8	3.9	7.9	6	1.25	0.80		95%

E 173	6.8	10	4.1	8	6	2.7	0.95	99%
E512	6.8	9.2	33.7	8	6	1.2	0.90	90%
E096	6.9	10.1	3.9	9.8	7.9	1.75	1.11	95%
E020	6.9	9.9	4	7.9	5.9	1.5	0.95	99%
E009	7	9.1	2.8	4.5	2.7	1.25	0.61	99%
E098	7	9	4.5	4.5	3	1.5	0.48	99%
E230	7	11.9	4.6	4.8	2.3	2.25	1.00	99%
E008	7.1	9	2.8	5.1	3.2	1	0.65	95%
E062	7.1	8.8	3	18.1	16.6 V		2.20	90%

Part No.	D	A	B	C	E	R	Wt. g	Material
E097	7.1	9.7	4.3	7.9	5.9	1.5	0.91	95%
E007	7.2	9.5	4	8	6	1.5	1.00	90%
E102	7.2	9.9	4.8	5	3	1.5	0.62	95%
E103	7.2	9.9	4.8	7.6	6	1.5	0.80	95%
E333	7.3	9.7	3.2	6.9	5	1.5	1.05	Ti
E006	7.3	9.4	3.9	7.5	4.9	1	1.05	99%
E095	7.3	9.5	3.9	9.1	7	1.5	1.16	95%
E123	7.3	10	4.7	13.1	11.1	1.75	1.30	90%
E080	7.4	12.3	1.9	5.7	4	1	1.40	Ti
E194	7.4	9.4	4.5	6.9	5	1.75	0.87	99%
E106	7.4	9.6	5.4	9	7	1.25	0.81	95%
E110	7.5	10.4	3.4	18	15	2.5	2.60	90%
E100	7.5	9.7	4.4	7.1	5	1.5	0.90	95%
E099	7.5	9.7	4.4	10.9	8.9	1.5	1.40	Ti
E105	7.5	9.8	5.3	9.5	8	1.5	0.90	95%
E270	7.5	9.5	5.4	13.4	11.4	1.5	1.14	95%
E101	7.6	10.7	4.7	8.8	7	1.5	1.11	95%
E197	7.6	15 4. 2		12.2	8.3 V		2.94	Ti
E045	7.7	10	3	21	17.9	2	3.20	95%
E229	7.8	14.7	4	11.9	8 V		3.10	99%
E195	7.8	9.8	4.9	6	3.6	1.5	0.83	99%
E104	7.8	10	5	7.2	5.2	1.5	0.94	95%
E255	7.9	12	4.1	12.5	7.7	2.25	2.70	95%
E410	8.3	11	5	8	6	1	1.15	96%
E022	8.5	10.6	4.8	9.9	7.9	1	1.60	95%
E276	8.6	10.6	4.8	6	3.9	1.5	1.50	95%
E125	8.8	10.4	2.8	9.4	7.5 B		1.63	95%
E278	8.8	10.7	4.8	13.2	11.1	1.5	2.20	95%

Part No.	D	A	B	C	E	R	Wt. g	Material
E411	8.8	12.8	6.3	15.4	12.9	2	2.10	95%
TE368	8.9	12	5	14.9	13	10.9	2.00	WC
E227	9	12	3.5	10.9	5	1	3.24	99%
E277	9	12.7	6.3	7.6	5	1.75	1.50	92%
E208	9.1	13.7	5	14.6	10.7	2.5	3.40	90%
E124	9.1	15	5	15	11.6	2.25	3.37	90%
E258	9.1	11.8	5.6	8.3	7	1.75	1.40	99%

E107	9.3	12	6	7.3	5.6	1.5	2.00	95%
E023	9.3	11.9	6.2	6.6	4.1	1	1.25	95%
E057	9.4	11.7	4.8	10	7	1.2	2.00	95%
E128	9.5	12.5	5.2	32	27	2.25	6.30	90%
TE358	9.5	11.8	5.5	5	3.4	11	2.00	WC
TE005	9.5	11.9	5.5	5.4	3.7	4.5	2.50	WC
E267	9.5	12.1	6.2	10.5	8.3	1.5	1.85	Ti
E308	9.6	14.7	5.3	25	22	1.5	5.50	95%
E355	9.8	12	5	13	9	2	3.10	95%
E117	9.8	13.9	5.3	20	16	2.5	5.25	90%
E252	9.8	11.4	6	13.4	12	2.5	2.30	Ti
E067	9.8	14	6.5	13	8	1.75	3.30	95%
E143	9.9	11.8	5	9	5.5	2	2.20	99%
E049	9.9	12	5	15	11	1.5	3.55	95%
E111	9.9	12.2	7	11	9	1.5	1.70	95%
E038	10	16	4	10.9	7.8	2.75	3.65	95%
E135	10	13	5.1	9	6	2.25	2.30	99%
E309	10	14.7	5.2	25	22	1.5	6.00	95%
E335	10	14	6.7	9.6	6.5	2	2.15	99%
E118	10.1	12	6.4	75	70	3.5	12.70	90%
E037	10.7	13.9	6.4	13	9.9	2	3.15	90%
E108	10.9	14.1	6.5	12	9.4	2.25	3.00	95%
E271	11	13.9	7.7	7.3	4.9	1.5	1.50	95%
E268	11.1	14.1	7.7	12.6	10.1	2	2.68	95%
E235	11.3	14	7.1	9	7	2	2.30	95%
E231	11.4	15	5	12.7	8.9	2	4.62	99%
E237	11.6	15	5.5	9.5	7	2.75	3.20	95%
E211	11.8	13.4	6.8	4.7	3	1.75	1.34	Ti
E024	11.9	15.4	7.7	10.2	7.2	1.5	3.05	95%
TE338	11.9	16	7.9	16.5	13.3	18	2.50	WC
E036	12	15.4	7.7	10	7.2	2	3.10	99%

Part No.	D	A	B	C	E	R	Wt. g	Material
TE332	12	15	8	10	6	11.3	3.00	WC
TE339	12	16	8	16.5	13.3	20	2.50	WC
E279	12.1	18	8.7	19	16	2	5.00	99%
E157	12.4	16	8.7	13.9	10.9	2	3.83	95%
E059	12.5	15.8	8.7	10.3	7.3	1.5	3.00	95%
E331	12.7	16	8	8	6	2	2.30	95%
E234	12.7	18	8.7	18.9	15.9	2.5	5.44	95%
E146	12.8	18	8.7	11	8	2.75	3.80	95%
E274	12.8	16	8.8	14	11	2.25	1.50	95%
E381	13	18	7	11	7	2	48.00	97%
E380	13	18	7	14	11	2	2.00	99%
E035	14	15.9	9.8	5.9	3.9	1.5	2.00	99%
E275	14.3	19.6	9.8	17	14	2.75	2.00	95%
E342	14.5	22.5	10.4	20.1	15.1	3.5	9.40	99%
E254	15	17.8	10.2	15	10	2	6.40	99%
E149	15.1	19.6	9.1	73.6	68.8	3	30.80	95%

E282	15.3	19.6	9.8	17	14	2.75	7.65	95%
E291	15.3	19.5	9.9	8.4	5.5	2.5	4.15	95%
E052	15.4	19.7	9.9	13.6	9.9	2.25	6.60	95%
E500	15.5	27	3.2	18.9	14.9	12	16.00	99%
TE357	15.9	18.6	9.9	14.8	12.8	25.5	1.50	WC
TE356	16	18.5	4.4	15.7	12.5	45	5.50	WC
E130	16	24.8	9.2	35.3	29.3	6	23.00	95%
E196	16.1	21.9	12.2	11	7.2	3	5.40	95%
E384	17	21.6	13	16.2	13	2.5	7.20	99%
E385	17.3	9.8	4.1	7.9	6	2	0.90	99%
E412	18	23	10	20	12.5	1.6	10.00	99%
E054	18	22	12	14	10	2.6	8.70	99%

Part No.	D	A	B	C	E	R	Wt. g	Material
E266	18.9	21.5	14.5	24.7	20	1.75	9.95	99%
E129	19	25	10	32	25	5.5	25.80	95%
E145	19	20.9	14	9	7	1.75	4.15	95%
E292	19	20.3	14.2	9.1	7.1	1.5	4.10	99%
E326	19.8	30	5.2	19.9	14.8	1.5	29.00	99%
TE337	20	22	12	25.4	22.1	76	2.50	WC
TE035	20	24	15.9	28.5	25	51	2.00	WC
TE334	20	23.8	15.9	28.5	25.3	51	1.50	WC
TE359	20	22	18	25.4	22	74	2.50	WC
E161	21.8	35	10.5	42.4	35.6	5	51.20	90%
E408	21.8	28.2	16	8	5	2	7.00	95%
E064	21.8	28.5	16.2	14.3	9.5	3	11.70	95%
E041	22	28	13	14	9.1	2	16.50	99%
E288	23.9	30	18.9	10.9	6.9	2.5	10.15	Ti
E327	25	35.1	10.2	19.8	14.7	1.75	39.00	99%
E261	29.9	34.8	20.1	24.8	19.9	4	36.10	95%
E328	30	40.1	15	20	14.8	1.75	50.00	99%
E409	32	36	25	16	13	2	19.00	99%
E042	35	38	24.1	11	8	4	19.40	90%
E043	41.3	47.2	32.8	10.7	6.7	1.5	24.80	95%